



M10 SL* (8 HOLES)

MARKED ON PLATE WITH STEEL TYPES.

Note: The SELF-LOCK threads, which are marked with SL*, must be made in accordance to the SIMRAD procedure 842-202125.

SELF-LOCK taps can be supplied by SIMRAD.

(*) NOTE: For keel installation, size of plate should be adapted to keel design.

SURFACE TREATMENT:
 1. SAND BLASTED AFTER GRINDING TO SA.2.5
 2. ONE COAT OF RED FERRIC OXIDE PRIMER.

2	1	PLATE	S355J0 (St. 52)	12x570x800					
1	1	RING	S355J0 (St. 52)	ø520x420x75					
ITEM	Q'TY	DESCRIPTION	QUALITY	DIMENSION					
REV./SIGN	8981	TW	D	KTP	E	DMJ			
DATE	93.05.27	00.02.01	02.04.16						
PROJ. METHOD			UNLESS OTHERWISE STATED, TOLERANCE:		PARTS LIST	SIMRAD A KONGSBERG Company			
SCALE	1:2.5		DIM: ISO 2768-mK		THREAD: 6g/6H	SHEET 1	OF 1	SH. SIZE: A2	REV.: E
DRAWN	89.10.25	L.F	MOUNTING RING			499-074076			
CHECKED	89.11.09	RLN	TRANSUCERS						
APPROVED	89.11.09	HB	38-7/ES38			FILE NO: 530-79			